CLASS A PRE-TRIP

FRONT OF TRUCK

LIGHTS REFLECTORS MARKER LIGHTS

NE

have a set of the

Clean, Clear, not Cracked or Broken Proper Color and Securely Mounted.

WHEEL

TIRE (I-C-D) Inflation, Condition (abc) Depth Properly inflated No Abrasions, Bulges, Cuts

Depth of 4/32"

RIM

No bends cracks, rust no illegal welds LUG NUTS

Not loose or missing. No shiny threads or rust trails.

AXLE SEAL

Proper level, not cracked no leaks

BRAKES

Brake Hose ABC no cracks, no leaks, securely mounted

Brake Chamber Securely mounted not bent, no leaks BBC

SLACK ADJUSTER AND PUSH-ROD

Slack Adjuster has no more than 1 inch of play. Push-rod not loose, bent or missing

BRAKE DRUM AND LININGS

Brake Drum has no cracks oil or grease Linings are minimum 1/4 inch

SUSPENSION

SPRINGS AND SHOCKS Springs not shifted crissored cracked or broken.

Shock absorbers mounted securely not dented or leaking.

Spring Mount

Not cracked, bent or missing any nuts/bolts U-Bolts

Not shifted, loose, or missing any nuts/bolts

STEERING COMPONENTS

STEERING BOX AND HOSES

Steering box is securely mounted no missing bolts

Hoses ABC not cracked or leaking

STEERING LINKAGE

PITTMAN ARM, not bent broken cracked DRAG LINK not bent broken cracked STEERING KNUCKLE not worn or loose TIE ROD not bent broken cracked ball joint not loose

Check that joints are not worn or loose, check for loose or missing nuts, bolts, or cotter keys.

ENGINE COMPARTMENT

OIL LEVEL

Not leaking Proper level

POWER STEERING FLUID

Not leaking Proper level HOSES No ABC (Abrasions, Bulges, Cuts)

POWER STEERING PUMP Gear Driven Securely Mounted

AIR COMPRESSOR

Gear Driven Securely Mounted Hoses ABC no cracks or leaks

COOLANT

Is the proper level Not Cracked Not Leaking Hoses have no ABC no Abrasions, Bulges, Cuts.

ALTERNATOR

Mounted securely Wires are not frayed cracked or loose Belt driven no more than 3/4 inch of play Belt is not frayed or cracked

WATER PUMP

Mounted securely with nuts or bolts Not leaking Belt driven, no missing bolts,

Hoses ABC no Abrasions, Bulges Cuts

BELT DRIVEN COMPONENTS TO CHECK: Alternator

Check belt for tightness and no more than 3/4 inch play. Hoses

Check ALL hoses for cracks or leaks